

WRANGELL AIRPORT ARPORT LAYOUT PLAN

WRANGELL ALASKA

2004

PREVIOUS REVISION DATE: 7-24-2001

APPROVED:

ANDY HUGHES, CHIEF OF PLANNING

FAA AIRSPACE REVIEW NO: 2004-AAL-87-NRA

FAA APPROVAL DATE: ///S//S/
BY: January Division, Alaska Region, AAL-610

SUBJECT TO CONDITIONS IN LETTER DATED:


7-24-2001 PREVIOUS ALP FAA APPROVAL DATE:_

SHEET INDEX

COVER SHEET & INDEX	
VICINITY MAP & DATA TABLES	
RUNWAY PLAN AND PROFILE	
AIRPORT TERMINAL AREA PLAN	
AIRPORT LAYOUT PLAN PROPOSED PROJECTS	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
APPROACH SURFACES PLAN & PROFILE	
F.A.R. PART 77 SURFACES	A
F.A.R. PART 77 SURFACES NON-TERRAIN OBSTRUCTIONS	== 4 = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1 = 1
F.A.R. PART 77 OBSTRUCTION TABLES	*****************************
AIRPORT LANDUSE PLAN	E S
AIRPORT PROPERTY PLAN	
NARRATIVE REPORT	***************************************

RUNWAY DATA		RUNWAY 10-28		
- IONWAI DAIA	EXISTING	ULTIMATE		
APPROACH SPEED CATEGORY /AIRCRAFT DESIGN	N GROUP	C-III	SAME	
RUNWAY DIMENSIONS	vyun,	150' x 6000'	SAME	
RUNWAY BEARING		S 59° 42' 01" E	SAME	
RUNWAY 10 INSTRUMENTATION		Non-Precision	SAME	
RUNWAY 28 INSTRUMENTATION		Visual	SAME	
RUNWAY OBJECT FREE AREA		800' x 8000'	SAME	
RUNWAY SAFETY AREA		500' x 7,600'	SAME	
OBSTACLE FREE ZONE		400' x 6400'	SAME	
RUNWAY APPROACH SURFACES: 10/28		34:1/ 20:1	SAME	
RUNWAY 10 APPROACH VISIBILITY MINIMUMS		1.25 MILES VIS	SAME	
RUNWAY LIGHTING		MIRL	HIRL	
RUNWAY MARKING		Precision	Precision	
EFFECTIVE RUNWAY GRADIENT (in %)		0.28	SAME	
PAVEMENT MATERIAL		Asphalt (Grooved)	SAME	
PAVEMENT STRENGTH (in thousand lbs.) 1		75(S)/175(D)/175(DT)	SAME	
RUNWAY PERCENTAGE WIND COVERAGE		98.87%	SAME	
RUNWAY 10 END COORDINATES	LATITUDE	N 56° 29' 18.95253"	SAME	
NAD'83	LONGITUDE	W 132° 22' 56.99442"	SAME	
RUNWAY 28 END COORDINATES	LATITUDE	N 56° 28' 48.16365"	SAME	
NAD'83	LONGITUDE	W 132° 21' 25.76658"	SAME	
RUNWAY TOUCHDOWN ZONE ELEVATION: 10/28		39.94/44.00	39.94/44.00	
RUNWAY PROTECTION ZONE DIMENSIONS				
INNER WIDTH		500'	SAME	
OUTER WIDTH:		1010'-	SAME	
LENGTH		1700'	SAME	
CRITICAL AIRCRAFT (C-III)	Boeing 737-200	Boeing 737-400		
NAVIGATIONAL AIDS: RUNWAY 10		VOR/DME NDB LDA/DME VASI-4 REIL	VOR/DME NDB LDA/DME PAPI MALSR	
NAVIGATIONAL AIDS: RUNWAY 28		VASI-4 REIL	PAPI REIL	

1 Pavement strengths are expressed in single (S), dual (D), dual tandem (DT), and/or double dual tandem (DDT), wheel loading capacities.



×2660 ft 28 27 WRANGELL PEAK /RYNDA \\
ISLAND { ×3747 ft KADIN 34 ISLAND 36 ×1302 f 32 36 ×2345 ft ×1745 ft MOUNTAINOUS TERRAIN 9 SOKOLOF GREYS ISLAND ISLAND 11 MAINLAND 8 \\ 17500 ft WRANGELL AIRPORT LIESNOL **ISLAND** Pt. Highfield Eastern 21 FERRY TERMINAL VANK Passage ĪSLAND WRANGELL () FIVEMILE 28 *ISLAND* Zimovia St WRANGELL ⁻ISLAND MILES WORONKOFSKI ISLAND T 62 S, R 83 E, SEC 13 T 62 S, R 83 E, SEC 24 T 62 S, R 84 E, SEC 19

COPPER RIVER MERIDIAN
U.S.G.S. PETERSBURG B-1, B-2, C-1, C-2

AIRPORT LOCATED AT NE CORNER PETERSBURG B-2

AIRPORT DATA	3		
AIR OR DATA		EXISTING	ULTIMATE
IACO/National Airport Identifier		PAWG/WRG	SAME
APPROACH SPEED CATEGORY /AIRCRAFT DESIGN (GROUP	C-III	SAME
AIRPORT ELEVATION (BASIS OF DATA NAVD88)		44 MSL	SAME
MEAN MAXIMUM TEMPERATURE OF HOTTEST MONTH		65.3° F	SAME
AIRPORT REFERENCE POINT	Latitude	N 56° 29' 03.56011"	SAME
(ARP) COORDINATES NAD 1983	Longitude	W 132° 22' 11.37538"	SAME
TAXIWAY LIGHTING		MITL	SAME
TAXIWAY MARKING		HOLD LINE, CENTERLINE	SAME
TAXIWAY WIDTH (A/B/E)			50'
TAXIWAY WIDTH (C/D)*		90'/25'	90'/50'
TAXIWAY SAFETY AREA WIDTH (A/B/E)			118'
TAXIWAY SAFETY AREA WIDTH (C/D)*		118'/49'	118'/118'
TAXIWAY OBJECT FREE AREA WIDTH (A/B/E)			186'
TAXIWAY OBJECT FREE AREA WIDTH (C/D)*		186'/89'	186'/186'
AIRPORT and TERMINAL NAVIGATIONAL AIDS	RMINAL NAVIGATIONAL AIDS		VOR/DME
		NDB	NDB
		LDA/DME	LDA/DME
		Rotating Beacon	Rotating Beacon
		AWOS	AWOS


* Taxiway names are Ultimate Existing Taxiway A will be renamed Taxiway C Existing Taxiway B will be renamed Taxiway D

NON STANDARD CONDITIONS					
ITEM	EXISTING	STANDARD	ULTIMATE		
RUNWAY 10 RSA BEYOND END	600,	1000'	600'		
RUNWAY 28 RSA BEYOND END	1,000'	1000'	1000'		
TREES/TERRAIN	OBSTRUCTION	NO OBSTRUCTION	OBSTRUCTION		

There are no OFZ Penetrations for this airport.

There are no Threshold siting surface object penetrations for this airport.

	1	LEGEND
EXISTING	PROPOSED	DESCRIPTION
		AIRPORT PROPERTY LINE
•	0	AIRPORT REFERENCE POINT (ARP)
*	≎	AIRPORT ROTATING BEACON
4444		BUILDING CONSTRUCTION
— — BRL		BUILDING RESTRICTION LINE (BRL)
		DRAINAGE
		FACILITY CONSTRUCTION
		FENCING
B VASI B	EDDS PAPI	NAVIGATIONAL AID INSTALLATION
		ROADS
		SHORELINE
• .		RUNWAY END IDENTIFICATION LIGHTS (REIL)
****		RUNWAY THRESHOLD LIGHTS
34 35 3 12		SECTION CORNER
9		SEGMENTED CIRCLE/WIND INDICATOR
1080		TOPOGRAPHIC CONTOURS
	-	WIND INDICATOR (Lighted)
-		SURVEY MONUMENT



PLANNED: VS
DRAWN: VS
CHECKED: VS

APRON DIMENSION

STATE OF ALASKA

DEPARTMENT OF TRANSPORTATION

AND PUBLIC FACILITIES

SOUTHEAST REGION PLANNING

230' x 1,170'

230' x 1,560'

PREVIOUS REVISION DATE: October 5, 2005

APPROVED:

DATE:

VERNE SKAGERBERG, TRANSPORTATION PLANNER, FOR ANDY HUGHES, CHIEF OF PLANNING


AIRSPACE REVIEW NO: 2004-AAL-87-NRA	BY	DATE	REVISIONS	
APPROVAL DATE: 2812	·	THE STATE OF THE S		
AIRPORT DIVISION, ALASKA REGION, AAL-610		-		
BJECT TO CONDITIONS IN LETTER DATED: 2		1		
EVIOUS ALD TAA ADDROVAL DATE. October 5, 2005				


WRANGELL AIRPORT 2

AIRPORT LAYOUT PLAN

VICINITY MAP AND DATA TABLES

OF 12





0 300 500 1,000 SCALE: 1"= 400'

PLANNED: v.s. STATE OF ALASKA

DEPARTMENT OF TRANSPORTATION

AND PUBLIC FACILITIES

SOUTHEAST REGION PLANNING

PREVIOUS REVISION DATE: October 5, 2005
APPROVED:


DATE: DATE: VERNE SKAGERBERG, TRANSPORTATION PLANNER, FOR ANDY HUGHES, CHIEF OF PLANNING


Wrangell Airport
Airport Layout Plan


SHEET


OF


15












DESCRIPTION	EL. (MSL)	OBSTRUCTION	OBSTRUCTION DESCRIPTION	DISPOSITION
101. TREE	EL. 133	YES	14' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
102. GROUND	EL. 73	YES	32' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
103. GROUND	EL. 80	YES	24' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
104. GROUND	EL. 84	YES	21' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
105. GROUND	EL. 77	YES	34' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
106. GROUND	EL. 73	YES	35' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
107. GROUND	EL. 87	YES	36' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
108. TREE	EL. 152	YES	37' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
109. TREE	EL. 137	YES	38' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
110. TREE	EL. 139	YES	12' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
111. TREE	EL. 136	YES	13' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
112. TREE	EL. 127	YES	32' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
113. TREE	EL. 130	YES	33' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
114. GROUND	EL. 69	YES	34' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
115. GROUND	EL. 66	YES		REMOVE
116. GROUND	EL. 64	YES		REMOVE
117. GROUND	EL. 61	YES	15' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
118. TREE	EL. 108	YES	1' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
119. TREE	EL. 130	YES	36' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
120. TREE	EL. 106	YES	37' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
121. GROUND	EL. 56	YES	38' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
122. GROUND	EL. 51	YES	39' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
123. GROUND	EL. 53	YES	3' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
124. GROUND	EL. 52	YES	4' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
125. TREE	EL. 113	YES	5' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
126. TRÉE	EL. 106	YES	17' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
127. TREE	EL. 104	YES	16' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
128. TREE	EL. 108	YES	27' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
129. TREE	EL. 106	YES	28' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
130. TREE	EL. 139	YES	29' OBSTRUCTION TO 34:1 NONPRECISION APPROACH	REMOVE
131. TREE	EL. 154	YES	21' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
132. TREE	EL. 171	YES	22' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
133. TREE	EL. 137	YES	4' OBSTRUCTION TO 34:1 NONPRECISION APPROACH	REMOVE
134. TREE	EL. 165	YES	5' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
135. TREE	EL. 169	YES	15' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
136. TREE			24' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
137. TREE	EL. 185	YES	25' OBSTRUCTION TO 7:1 TRANSITIONAL SURFACE	REMOVE
138. TREE	EL. 194	YES		
	EL. 198	YES		REMOVE
139. TREE	EL. 203	YES		REMOVE
140. TREE	EL. 245	YES	51' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
141. TREE	EL. 211	YES	52' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
142. TREE	EL. 213	YES	19' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
143. TREE	EL. 203	YES	9' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
144. TREE	EL. 235	YES	10' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
145. TREE	EL. 203	YES	9' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
146. TREE	EL. 213	YES	10' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
147. TREE	EL. 210	YES	16' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
148. TREE	EL. 198	YES	17' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
149. TREE	EL. 202	YES	18' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
150. TREE	EL. 197	YES	3' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
151. TREE	EL. 227	YES	33' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
152. TREE	EL. 215	YES	21' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
153. TREE	EL. 232	YES	22' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
154. TREE	EL. 220	YES	26' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
155. TREE	EL. 207	YES	13' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
156, TREE	EL. 222	YES	28' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
157. TREE	EL. 255	YES	61' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
158. TREE	EL. 209	YES	15' OBSTRUCTION TO THE HORIZONTAL SURFACE	REMOVE
159. TREE			TREES OBSTRUCTION TO HORIZONTAL SURFACE	REMAIN
160. GROUND	EL. 194+ EL. 194	YES	GROUND OBSTRUCTION TO HORIZONTAL & CONCICAL	
LULU CHALLUMAN	1 日 194	YES	GROOND ODSTRUCTION TO HURIZONTAL & CUNCICAL	REMAIN

FEATURES 159 & 160 SHOWN ON SHEET 7.



NOTE:

SEE SHEETS 7 & 8 FOR OBSTRUCTION LOCATIONS

PLANNED: DJG JJJ 7-27-05 DRAWN: TJH/LW

DEVELOPED BY HDR ALASKA, INC.

CHECKED:

STATE OF ALASKA

DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES

SOUTHEAST REGION PLANNING

PREVIOUS REVISION DATE: 7-24-2001 APPROVED VERNE SKAGERBERG, TRANSPORTATION PLANNER, FOR ANDY HUGHES, CHIEF OF PLANNING

FAA AIRSPACE REVIEW NO: 2004-AAL-87-NRA BY DATE REVISIONS FAA APPROVAL DATE: FAA AIRPORT DIVISION ALASKA RECON, AAL-610 10/08/08 SUBJECT TO CONDITIONS IN LETTER DATED: 07-24-2001 PREVIOUS ALP FAA APPROVAL DATE:

ITEMS 19-27, 40, 41-43, 45-47, 49, 51-56 LISTED AS GROUND OR UNPAVED ROAD ARE LOCATED ON THE KNOLL WEST OF THE APRON.


ITEMS 80-91, 97-100, 102-107, 114-117, 121-124 LISTED AS GROUND OR UNPAVED ROAD ARE LOCATED EAST OF THE APRON AND WITHIN THE PARALLEL TAXIWAY RESERVE OR BETWEEN THAT RESERVE AND THE RUNWAY.


WRANGELL AIRPORT

AIRPORT LAYOUT PLAN F.A.R. PART 77 SURFACE

OBSTRUCTION TABLES

SHEET





Rationale: Currently no passenger loading/unloading area exists and passengers who

park vehicles must cross a busy two way road to reach the terminal. Additional short and long-term parking spaces are presently needed to handle the demand.

2. RUNWAY AND TAXIWAY A SURFACE OVERLAY

\$3,460,000

\$2,400,000

Resurface and groove Runway, resurface Taxiway A, pave runway shoulders, repave pavement near hardstand.

Rationale: Present runway surface and grooving is worn; regrooving is needed to ensure safe operations in southeast Alaska's wet environment. Taxiway A presently has areas of longitudinal and transverse cracking and shallow depressions. The gravel shoulders have higher maintenance costs and present a FOD hazard to aircraft. Ponding occurs on the apron adjacent the hardstand in wet weather.

3. TAXIWAY B CONSTRUCTION

Construct and stripe new parallel taxiway (50'x525') and new perpendicular taxiway (50'x 500') at the west end of the terminal area.

Rename Taxiways: Taxiway A to C, Taxiway B to D

Rationale: Taxiway access to the threshold reduces back-taxiing and improves safety by eliminating the 180-degree pivot turn at Runway end. The new taxiway configuration will reduce facility maintenance costs by allowing jet aircraft to taxi parallel to the terminal area, removing jet blast effects on buildings and equipment. The present jet parking area requires jet aircraft to turn more than 120 degrees to return to the runway. This sweeping turn hits the terminal buildings and aviation support equipment with jet blast.

4. SEAPLANE RAMP RELOCATION AND ACCESS TAXIWAY

Relocate ramp outside RSA; construct seaplane ramp access taxiway (35'x1,830'); stripe taxi lanes.

Rational: The present seaplane ramp requires access via taxiway A and Runway 10; thereby requiring airport personnel to escort pilots to and from the seaplane ramp. The new seaplane ramp location is usable without interfering with operations on runways 10/28. The existing ramp can only be used during high tides. The existing ramp will be filled over to create the RSA.

5. RUNWAY SAFETY AREA (RSA) EXPANSION/ PART 77 SURFACE SURFACE EXCAVATION/ WATER TANK RELOCATION

\$48,800,000

Construct new RSA: Extend RSA length to 1,000 feet on each runway end and overall width to 500 feet. Remove obstruction (250-foot knoll) adjacent to Runway 10 and use for RSA fill, relocate water tank.

Rationale: Wrangell runway RSA is deficient in length and width and there is a turbulence inducing knoll adjacent the approach end of Runway 10. This project would reduce the size of the knoll to generate the material needed to expand the RSA to improve the safety of aircraft operations. It will also remove the knoll's penetration into the Part 77 airspace. A community water tank located on the knob will require relocation.

6. AIRPORT PERIMETER FENCE AND GATE IMPROVEMENTS

Relocate existing fence to accommodate Phase I airport improvements. Improve fence (raise to 10', install barbed outriggers and skirts), improve access gates.

Rational: These fence and gate improvements must occur to accomodate apron and RSA expansion and reduce unauthorized human and wildlife incursions to the runway and terminal

7. SEWER LINE REALIGNMENT

Realign sewer line to improve grade in terminal area. Complete waterline to DOT&PF Maintenance building.

Rationale: Frequent backups in the existing sewer line pose a health concern and are a regular maintenance item.

8. OBSTRUCTION REMOVAL

\$16,000

Remove trees and relocate utilities listed in tables on sheet 9

Rationale: Remove as many of the Part 77 obstructions that is economic to do so. Obstructions will still remain in the form of a large mountain and the trees

PHASE | PRIORITIES (5 to 10 Years)

1. TAXIWAY D UPGRADE

\$227,000

Replace culvert with one of sufficient strength, increase clearance to C-III standards (50'x800' plus 20' shoulders).

Rationale: The use of Taxiway Bravo (renamed to taxiway D) by jet aircraft in combination with and the construction of the connecting taxiway at the approach end of runway 10 will improve overall jet aircraft circulation to and from the terminal apron and prevent unintended use of taxiway Bravo by jet aircraft without proper payement strength and

2. WEST APRON/ COMMERCIAL LEASE LOT, ROAD AND PARKING DEVELOPMENT

\$803,000

Expand terminal apron west (87,500 sq. ft.), develop three lease lots (15,000 sq. ft. ea.). Extend terminal access road and parking westward for new lease lot access.

Rationale: This project is needed to satisfy the forecast demand, and meeting this demand would provide economic opportunities to the community.

3. HELIPAD DEVELOPMENT

Develop helipad in new west apron. Install signage to prohibit helicopters on GA apron.

Rationale: Under the existing condition, helicopter operations occur on either the general aviation or terminal apron. Operations in these areas cause further congestion in these areas and pose a safety and health risk due to rotor wash. This project relocates the helipad to reduce conflicts and improve safety.

4. FIRE TRUCK REPLACEMENT

\$600,000

Replace fire truck.

Rationale: Need to replace the 1982, 1,500 gallon vehicle to ensure and improve ARFF response capability and safety. Wrangell airport has an ARFF index A.

5. NAVIGATIONAL IMPROVEMENTS

\$1,200,000

Upgrade GPS approach

Install approach/dighting for Runway 10

Install backup generator

Install precision approach path indicators (PAPI)

Install compass calibration pad.

Rationale: Use GPS capability to provide improved horizontal and vertical approach information for possible lower minimums. Upgrade approach lighting for better runway environment visibility in lower

Precision approach path indicators (PAPI) will provide better glide slope definition than the VASI lights in use.

PHASE III PRIORITIES (10 to 20 Years)

1. MAINTENANCE / PERIMETER ROAD DEVELOPMENT \$2,600,000

Construct 12'x4,400' road on the airport side of the perimeter fence for maintenance access to approach end of Runway 28.

Rationale: This road will allow easy and frequent inspection of the integrity of the security fence. It will also allow maintenance vehicles access to the east end of the runway without driving down the runway.

FUTURE PROJECTS (20 + Years)

1. PARALLEL TAXIWAY A DEVELOPMENT/ CONSTRUCT TAXIWAY E

2. GENERAL AVIATION TIE DOWN EXPANSION

3. ACCESS ROAD RELOCATION

FORECASTS						
YEAR	2000	2005	2010	2020		
ENPLANEMENTS	17,809	17,854	17,898	17,988		
AIR CARRIER*	10,151	10,177	10,202	10,253		
COMMUTER / AIRTAXI	7,658	7,677	7,696	7,735		
OPERATIONS		27.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1	The state of the s	eseeringa ka		
TOTAL INSTURMENT OPERATIONS	1,908	1,913	1,917	1,927		
AIR CARRIER (B 737)	1,459	1,463	1,467	1,474		
COMMUTER / AIR TAXI	5,604	5,620	5,636	5,666		
GENERAL AVIATION		од _{ент} ине текспентичентиченто почет почет повет повет почет почет почет почет почет почет почет почет почет поче	Colon And And And Andread Annual Annu			
ITINERANT	1,883	1,886	1,890	1,896		
LOCAL	1,092	1,094	1,096	1,098		
TOTAL ANNUAL OPERATIONS	10,038	10,063	10,087	10,135		
AIRPORT REFERENCE CODE	C-III	C-III	C-III	C-III		
NUMBER OF BASED AIRCRAFT	28	29	30	31		
CRITICAL AIRGRAFT	BOEING 737-200	BOEING 737-200	BOEING 737-400	BOEING 737-400		
APPROACH SPEED (kts)	137	137	137	137		
WING SPAN	93	93	95	94		
WEIGHT: MAX TAKEOFF WEIGHT (lbs)	115,500	115,500	140,000	140,000		

^{*} ALL AIR CARRIER OPERATIONS ARE CONDUCTED WITH THE CRITICAL AIRCRAFT

REVISIONS

BY

DATE

PLANNED: DJG DAL 7-29-05 DRAWN: TJH/LW CHECKED:

STATE OF ALASKA

DEPARTMENT OF TRANSPORTATION AND PUBLIC FACILITIES

SOUTHEAST REGION PLANNING

PREVIOUS REVISION DATE: 7-24-2001 APPROVED:

ANDY HUGHES, CHIEF OF PLANNING

2004-AAL-87-NRA FAA AIRSPACE REVIEW NO: FAA APPROVAL DATE: /P/VT/DC

BY:
FAA AIRPORT DIVISION, ALASKA REGION, AAL-610, SUBJECT TO CONDITIONS IN LETTER DATED: 07-24-2001 PREVIOUS ALP FAA APPROVAL DATE:

WRANGELL AIRPORT AIRPORT LAYOUT PLAN NARRATIVE REPORT

DEVELOPED BY HDR ALASKA, INC.

VERNE SKAGERBERG, TRANSPORTATION PLANNER, FOR